

## Dal Degan Manda 300

### Anbauspritze 300 l



### Parameters

Name	Einheit
Tractor Motor Power	22-26 KW
Tractor Power	30-35 HP
Gewicht	125/135 kg
Höhe	1200 mm
Breite	2050 mm
Länge	1200 mm

### Beschreibung

Spraying group ideal for medium and large-sized farms. The frame is varnished and made of metal pipes. The tank consists of two parts: the main tank and hand-washing tank. Equipped with "BETA" boom, built with steel tubes and high resistant plastic resin nozzles-holder pipes, is mounted on sliding rails and adjustable at any height, single nozzle-holders are with check-valve. The filter has the possibility of self-filling from natural sources (wells, reservoirs for water accumulation, sources, etc.). The homogenization of the preparation is accomplished by a hydro-injector. The bottom hinge is realized in three points with a Ø22 / 28 mm sleeve. There is also the possibility of installing prochromic tubes, pressure regulators with multiple outputs and other equipment specified in the optional equipment.

### Standard features:

Two tanks: polyethylene with filter and cover 200/300L and hand-washing tank 15L with faucet;  
 Total emptying system;  
 Varnished steel frame;  
 The bottom hinge is realized with a Ø22 / 28 mm sleeve;  
 Three ways pressure regulator "Start 06 - Tecomec - Italy";  
 Dal Degan DL 260 NP pump (2 diaphragms, flow 60 L / minmaximum pressure 20 bar);  
 Filter (50mesh=300µm) GEOLINE with self-filling possibility;  
 Hydraulic injector TECOMECH with nozzle Ø1,25mm;  
 Plastic resin nozzles GEOLINE type AZ 0.2 for working pressure 3 - 4 bar, angle resin 110°;

### Haupt stammsitz

Agrohof Kft.  
 6064 Tiszaug, Bokros tanya 16.

### Vertrieb

+49 1525 1744472  
 info@agrohof.com

<https://agrohof.de/sku/d03-11510>

